

DA VINCI MARBLE

Moroccan Tile

Zellige, Bejmat, and Bahia


Zellige Tile



Bright White
2” x 2” (mesh-mounted)



Wet Sand
4” x 4”
2” x 2” (loose pieces)



Haze Green
4” x 4”
2” x 2” (loose pieces)




Savannah Moss
4” x 4”




Zen
4” x 4”
2” x 2” (loose pieces)



Amalfi Blue
4” x 4”
2” x 2” (loose pieces)



Tahoe Blue
4” x 4”




Spruce
4” x 4”




Fog
4” x 4”



Obsidian Black
4” x 4”



Dragon Green
4” x 4”



Red Dahlia
4” x 4”




DA VINCI MARBLE

Moroccan Tile

Zellige, Bejmat, and Bahia

Zellige Tile



Royal Velvet
4” x 4”



DA VINCI MARBLE

Moroccan Tile

Zellige, Bejmat, and Bahia

Bejmat Tile



Smoke White
2” x 6”



Whisper Blue
2” x 6”



Palm Desert
2” x 6”



Fez Green
2” x 6”



Blue Lagoon
2” x 6”

Stocked Mosaic Bahia



Bright White & Smoke White
Sheet Size 1.0 sq. ft.

Technical Information

SIZE	THICKNESS
4” x 4”, 2” x 2”	1/2”–5/8“
2” x 6”	5/8”
Mosaic Bahia 12” x 12”	1/2”

FLOOR	WALL	FROST RESISTANT	INDOOR	OUTDOOR
Yes*	Yes	No	Yes	Yes

WET AREA	POOL	VARIATION
Yes	No	High

**Light Residential/Traffic*

–Zellige, Bejmat, and Bahia materials sold by full box only
–10.77 SF per box (2”x2”, 2”x6”, 4”x4”)
–11.00 SF per box (Bahia / 2”x2” mesh-mosaics)
–All sizes are nominal
–As standard industry procedure, our recommendation is to order an additional 20% overage



DA VINCI MARBLE

Moroccan Tile

Zellige, Bejmat, and Bahia

Installation Guidelines

Please use this as a guide for general information regarding installation of Glazed Moroccan Zellige, Bejmat, and Bahia Mosaic tiles. Moroccan tile is a low-fired terracotta that is suitable for many applications including light traffic floors, walls, interiors, exteriors and water applications such as pools, fountains, and steam showers. Not suitable for freeze thaw applications.

Authentic Moroccan tiles have the following characteristics: pits in the glaze, chipped edges, shade variation, and irregularity in shape and size.

Installation

Prior to installation, pull tiles from different boxes to achieve optimal blend. Variation in color and/or thickness is the nature of Moroccan tile and is not a flaw.

DO NOT install from unblended boxes

Blending–Dry lay tiles from ALL BOXES to blend tiles for best appearance
Cleaning–Spray or soak all of the tiles in water to remove tile dust
Prepping–Level walls and floors
Adhering–Apply a layer of adhesive on the application surface
Back Buttering–Apply another layer of adhesive on the back of each tile
Placing–Set tiles into the adhesive one at a time
Spacing–Uneven edges require the use of wedge spacers (1/16” spacing is common)
Cutting–Cut with a diamond blade
Grouting–Applying sealer or using a grout release prior to grouting can be done. Grout glazed tiles with sanded or un-sanded grout. Grout will also fill in surface pits, chips and cracks.
Cleaning–Remove excess grout and grout film from the surface of the tiles
Sealing–Sealers will not penetrate the glazed surface, however sealing your grout is recommended

Maintenance

Tile cleaner, mild soap or PH neutral cleaners can be used

General Moroccan Zellige and Bejmat tile installation instructions have been supplied as a guideline. As with all tile installations, please refer to the TCNA Handbook and/or ANSI specifications for Ceramic Tile for complete instructions and consult your professional tile installer. Da Vinci Marble is not liable for tiles that have already been installed. Enjoy the long-lasting beauty and timeless elegance of Moroccan Tile.